XL400 PRODUCTIVITY APPLIANCE



with Large Digital Display



THE CHALLENGE

You need a simple and effective way to improve manufacturing productivity. A way to gather actionable information that exposes problem areas, and a way to inspire and motivate the people that have the greatest impact on productivity – your plant floor employees. You need information fast – and at your fingertips. Not buried in a report that is days or weeks old. With resources and budgets already stretched thin, somehow you need to produce more with less. And you need an easy and affordable solution with no software to install, no contracts to sign, and installation measured in hours – not weeks or months.

THE SOLUTION

Introducing the XL400 Productivity Appliance[™]. A "bolt-on" performance management tool that is so easy to use that it can be self-deployed in about an hour. The XL400 automatically tracks production in real-time and instantly delivers meaningful, accurate, and actionable information anywhere in the world. We call it *Data Anywhere, Data Everywhere*[™]. The integrated large area visual display informs, alerts, and motivates your plant floor employees, while the built-in Ethernet LAN connection delivers instant production reports and analytics to supervisors and managers—wherever they are. All from one, low-cost, fully-integrated hardware appliance.

THE PRICE

XL400 4"	4 to 12 Digits	From \$1,690	XL400 8"	4 to 8 Digits	From \$1,890
XL400 6"	4 to 8 Digits	From \$1,790	XL400 12"	4 to 6 Digits	From \$2,290

Production Reports Included!					Historical Analytics Included!							Browser-Based Data Included!						
																	-	
Shift Information					1 000 000	Stop Tana State C	and Court Inc.	to Canada Pres	or Convertient	and Second	Concerned in						Assembl	ty Call #1
Shift Starts Shift End: Shift 30:	00/15/2007	08:00-00 36:00:00 First Shift	Adead Cycles Takt Tisse: Average Cycle:	3.20000000 4.18000000 3.34000000	3 V16/367 96-90 3 V16/367 96-90 4 V16/367 96-90 5 V160	V16/2807 16:00 First SNR V16/2807 52:00 Secure SNR V16/2807 16:30 First SNR V16/2807 16:30 First SNR V16/2807 52:00 Secure SNR	5.900 6.875 5.717 6.341 5.425	120 130 500 400 349	8,198 1,198 1,929 1,942 1,942	5,854 6,737 5,119 5,348 5,214	94.54% 04.55% 01.07%	1111	Bata Anyakera, Bata fare	(Deputte	n Adm Andreiter	Trage Trage		
					A Longer of the	stracterit strat facund line	8.120	143	1.794	8.798	10.00%	65.27%	- Counters		Average Rate		- Current Rate (
Good Creek Reject Count Total Count		5,834 136 5,960	OLE Availability: Performance:	76.72% 76.29% 94.62%	8 V182367 67 00 9 V182367 16 30 30 V182367 67 00 11 V182367 67 00	MACHINE M.SO First Stat. Mischell 82:00 Second Stat. Mischell 83:00 First Stat.	6.384 7.347 5.020 5.822	000 437 404	1.545 1.545 1.827 1.627	8.151 8.910 4.019 4.315	10 40% 00 00% 00 00%	115h	Setal Count Good Count Reset Count	5,960	Total RPH Good RPH Reject RPH	813 796	Total RPH Good RPH Reject RPH	1,101
Average 87%		813	Quality	12.0%	12 V28/2887 67-00 13 V28/2887 95-30 14 V29/2887 67-00	NOV2007 16:30 First Shitt NOV2007 52:00 Second Shitt NOV2007 16:30 First Shitt	6.819 6.220 6.211	65 208 679 447	1.526 1.601 1.979	8.578 8.042 5.582	17 32%	61.00% 15.20%	000	78.71%	Target Counts	6.184	Goal Counter -	6,184
Production Tim					15 V2V2507 18.50	ACCOUNT IS OF Second Stat	P.008 6.515	447	1.967	6,591	82 72%	87.24% 87.22%	Availability	76.19%	Actual	5,834	Pieces to Goal	350
Run: 5	6.36.13	45.34% 18.21%	Targette and Grafe	6.104	N VOIDER NO. 30	ADS/2007 62:00 Second Shift	6.510	468	1.718	5.822	74.20%	05.34%		94.82%	Efficiency	14.34%		
Down: 1	1.27.25	18.21%	Advall	5.034	M N2938F 67:00	1/25/2807 16:30 Feat Shift	1.550	375	1,000	2 175	\$1.80%	51 82%- 71 82%	Quality	97.89%	Time Variance	0.23:55	Percent of Goal	94,24%
	0.40.00	8.33% 100.00%		-	30 V00000 W 30 30 V00000 V 00 31 V00000 W 30 32 V05000 V 00	VOX2007 82:00 Second DNR VOX2007 16:30 First Sec V25/2007 82:00 Second Set V25/2007 16:30 First Set	5.040 7.72e 9.710	347 101	1,000	5.602 7.625 9.000	12.01% 95.30%	64.70% 13-42%	Cycle Times Current Cycle Time (x) Last Cycle Time (x)	1.22	Production Til Run Time Down Time	5:25:13	Prod. Time Per Percent Run Percent Down	69.84% 18.21%
					25 V25/367 98.30	109/2007 02:00 Second Shift	6.952	298	1,981	6.367	79.79%	6.98	Average Cycle Time (s)	3.34	Setup Time	0:37:22	Percent Setup	3,62%
Standard 4	4.12.54	4.649			25 109-2107 16.30	NOTONIT 62:00 Second Shift	6.040	410	1.754	6.147	81.04%	61,20%	Standard Cycles	4.600	Standby Time	0:40.00	Percent Standby	8.32%
Small Stop: 1	11113	1,192 60			28 VCh2xxF 6F 08 27 VCh2xxF 95 30 28 V2x2xxF 8F 02	5/29/2007 16:30 Fest Set 5/29/2007 02:00 Second Set 5/29/2007 16:30 Fest Set	6.112 7.314 5.810	745 60 601	1,817 1,810 1,880	5.366 7.257 5.215	41 12% 05 20% 47 79%	41.43% 52.00% 51.33%	Silow Cycles Small Stops	1,192	Production Hode	Run	-	
					28 VORCENT 14.30	1/29/2007 82:00 Second Styll	1,857	488	1.045	1,000	96.20%s	17 15h	Standard Cycles Time	4:12:54				the second s
Geer Numbers		5.126	User Strings	Sateritar	at voicent is to	A DOCTOR \$2.00 Second State	1100	100	1426	1.022	AC APR	69.12%	Slow Cycles Time	111112	_	_	And in case of the local division of the loc	-

KEY BENEFITS

- A complete solution—plant floor scoreboard, production reporting system, historical analytics, and browser-based live data—all included.
- No software to install. Simply plug the XL400 into your LAN and it delivers instant plant floor performance data.
- No changes to your process. It's a "bolt-on" solution that easily connects to your existing process.
- No waiting. Instant production reports delivered in Excel[®], Word[®], and CSV formats.
- Live production data delivered directly to your desktop via a standard web-browser.
- Motivates plant floor employees to meet and exceed goals with real-time performance feedback.
- Eliminates time consuming and error-prone manual data entry.
- Tracks 100+ metrics including OEE, Target, Performance to Takt, Rate and Down Time.
- Exposes losses in real-time for immediate corrective action.
- Shows if process is on target (green), slightly deviating (amber), or requires immediate attention (red) on tricolor models.
- Adapts to your process with intuitive browser-based configuration tools.
- Field proven with thousands of installations across all major industries.
- Self-deployed in about an hour.
- FREE 90-day trial with expert technical support.



We Improve Manufacturing Productivity[™] = 1-877-767-LEAN = www.vorne.com

Shift Report - Assembly Cell #7							 In this fags interface - In the are facilities in may //1013.04.21 	4 29	ilerent Eigherer				
Shift Start Shift Ead Shift ID	50/15/2007	0000000 16-00-00 55% 55%	Maal Cy Take Tin Aver 10		1 contract of the second				Carlo Arpentera, Bala I				Y Cell #7
Good Coast Reject Coast Total Coast Asserage EPs		5034 136 139 139 139	Official August Parts Quart	ACCASES VICTORIA	A Journey Coller Contraction Coller Visional William Processes Visional William Processes Visional William Processes Visional William Processes	A STATE	in the second se	110 1.10 1.10	Counters Total Court Good Court Reject Court	1,000 3,020 3,020	Average Rate (RPH)- Tatai Rev 81) Gaug Alm 7% Report RPH 27	Current Rate (Tursi Alfer Geog Atres Argent Rifer	1,103 1,103 1,093
Ann Ann Diven	1 38 13 1 27 28 0 17 13	4145	10	A DESCRIPTION OF THE PARTY OF T	Children Artin Berning Berl orthogen of the Area and compare of the Area and compare and the Area and compare and the Area and compare was for the Area compare was for	5.001 6.005 7.000 9.000 7.000 7.000 7.000		NAME AND	OEE Assumity April and Destry	10 /14 m (4% m (2%) 97 80%	Target Counter Target 6,650 Actual 8,850 Efficiency 84,3450 Time Variance (8,2315)	Goal Counter Coal Paces to Goal Percent of Goal	6.161 250 34.34%
Standby: Total	4 12 54	4.540		A DESCRIPTION OF A DE A DESCRIPTION OF A DE	COUNT OF A Research and COUNT OF A Page and STOCKET THE Page and STOCKET THE APPROX AND COUNT OF A Page and And	4,007 4,200 4,201 7,000 4,201	1012144	121582	Cycle Times Carnet Cycle Time (8) Lett Collin Time (1) Assumpt Cycle Time (8)		Production Times Ruh Time 5.25.11 Down Time 1.07-25 Selup Time 0.07-25 Standty Time 0.07-25 Standty Time 0.017-20	Prod. Time Per Persent Rut. Persent Down Persent Simo- Persent Simo-	18.21% 8.62% 8.62%
Street Street	11112	4,649 1,197	115	Appropriate of an	second size Percent	1.910	100	100	Standard Cycles Size Cycles	4,648	Production Made Sta	(rear is an	

"SIX-IN-ONE" PRODUCTIVITY APPLIANCE™

The XL400 is an incredibly flexible performance management platform that combines six products into one simple package:

- Visual Display Informs, alerts, and motivates employees
- Production Monitor Tracks manufacturing performance
- **Data Warehouse** Manages real-time and historical data
- I/O Processor Provides flexible connectivity to your process
- Embedded Server Distributes data to managers everywhere
- Programming Platform Tailors operation to your process

VISUAL DISPLAY

The XL Visual Display provides instant performance feedback to the plant floor. Information that informs, alerts, and motivates your plant floor employees.

See Goals, Meet Goals

Goals are a powerful motivator, and the XL Visual Display establishes a shared set of goals for the plant floor. In fact, for most applications, the XL Visual Display is the fastest path to productivity gains. It channels people's natural competitive spirit and harnesses their desire to win by establishing SMART goals (Specific, Measurable, Attainable, Realistic, and Timely).

Focused Feedback

XL delivers the right information to the right people at the right time. It translates complex manufacturing data into easy-to-understand performance feedback. The result is a well informed, strategically-aligned workforce that is truly focused on improving productivity.

Customizable-Not Custom

Every production situation is unique. That's why XL makes it especially easy to select the metrics that are most meaningful for your plant floor. With 100+ metrics available "out of the box", XL easily adapts to your needs. Plant floor events are immediately reflected on the XL Visual Display, providing a direct link between action (line goes down) and reaction (operator resolves problem).



When the line goes down automatically display down time in red.

PRODUCTION MONITOR

The XL Production Monitor connects to your manufacturing process with plug-and-play simplicity. Seven integrated modules provide metrics and KPIs that are critical to understanding and managing your production: Counts, Rates, Cycles, Production Times, Visual OEE™, Targets, and Goals.

NO SOFTWARE TO INSTALL!

XL provides instant browser-

based access to production

reports, historical analytics,

and live plant floor data.

Easy Integration

Simply add one or two sensors and get a wealth of actionable information.

YOU PROVIDE	XL PROVIDES
One Sensor	Total Count, Current Rate, Average Rate, Current Cycle Time, Last Cycle Time, Average Cycle Time, Run Time, Last Run Event, Percent Run, Down Time, Last Down Event, Percent Down, OEE Availability
Second Sensor	Good/Reject Count, Percent Good/Reject, Good/Reject Rate, OEE Quality
ldeal Cycle Time	Standard Cycles, Standard Cycles Time, Slow Cycles, Slow Cycles Time, Small Stops, Small Stops Time, OEE Performance, OEE
Takt Time	Target Count, Pace Timer, Takt Timer, Count Variance, Time Variance, Efficiency
Goal	Pieces to Goal, Percent of Goal
Setup Switch	Setup Time, Last Setup Event, Percent Setup
Time Schedule	Standby Time, Last Standby Event, Percent Standby, Remaining Time

DATA WAREHOUSE

The XL Data Warehouse manages real-time and historical data with Registers and Streams.

Registers

Registers store real-time data such as the 100+ metrics generated by the XL Production Monitor. They also provide hundreds of "uncommitted" registers that can be loaded from PLCs, ERP systems, and other sources.

Streams

Streams store archived historical data, such as production records for the last 1,000 shifts and 1,000 jobs.

I/O PROCESSOR

The XL I/O Processor provides flexible connectivity to your production process.

Digital Inputs

Eight (8) digital inputs are standard, and can be expanded to twenty-four (24) with a sixteen-input expansion card.

Digital Outputs

One (1) relay output is standard. *Relay outputs are for annunciation only, and are not designed or intended for control applications.*

Communication Ports

Three (3) communication ports are standard: 10/100 Ethernet, RS-232 and RS-232/RS-485 (selectable).

©2008-2013 Vorne Industries, Inc. All rights reserved. Prices and specifications subject to change without notice. Please reference the Vorne Product Warranty Statement and Sales Terms and Conditions at www.vorne.com. Vorne Industries, Inc. makes no warranties express or implied except as expressly stipulated in our Product Warranty Statement. Free 90-day trial offer is for qualified manufacturing applications only. Vorne, Visual OEE, Productivity Appliance, Data Anywhere, Data Everywhere. and We Improve Manufacturing Productivity are trademarks of Vorne Industries. All other trademarks are the property of their respective owners.

EMBEDDED SERVER

The XL Embedded Server provides instant access to production data for supervisors and managers—from anywhere in the world—with no software to install.

Data Anywhere, Data Everywhere™

Supervisors and managers can view live production data and download shift and job reports in Excel®, Word®, and CSV formats—all via a standard web-browser.

Documentation Center

No lost manuals, no out-of-date information, and no digging for documentation. The XL Documentation Center delivers instant access to complete XL documentation direct from XL via web browser.

PROGRAMMING PLATFORM

The XL Programming Platform makes it easy to tailor XL operation to your specific requirements. Create application specific programs by simply stringing together predefined commands to achieve your desired operation.

Time Schedules and More

Programs can be automatically triggered by time schedules, inputs, presets, production state changes, and more.

Unlimited Applications

- Drive a stack light based on line speed or downtime
- Automatically display remaining time for breaks
- Create "custom" metrics and KPIs
- Create a maintenance call button with a response timer

SPECIFICATIONS

Visual Display

- 4" to 12" tall digits, 4 to 12 digit configurations
- Red LED or Tricolor (Red/Green/Amber) LED (4" only)

Digital I/O

- (8) Inputs 5 to 24 VDC Sink/Source (expandable to 24)
- (1) Output 1A, 120 VAC, SPDT Relay

Electrical

- Voltage: 100 to 240 VAC
- Power: 16 to 65 Watts (depending on model)

Mechanical

- XL400 4" (8.4" H x 16.3" W to 44.7" W x 3.5" D; 4-12 Digits)
- XL400 6" (10.4" H x 23.7" W to 45.3" W x 3.5" D; 4-8 Digits)
- XL400 8" (12.4" H x 29.7" W to 57.3" W x 3.5" D; 4-8 Digits)
- XL400 12" (16.4" H x 43.5" W to 73.8" W x 3.5" D; 4-6 Digits)

XL-A COMPLETE PRODUCT FAMILY

XL is much more than a product—it's a complete platform for production monitoring and performance management. The only difference between XL models is the type of visual display. Simply select the most appropriate display for your application.

- XL400 Single line with 4" to 12" digits (starts at \$1,690)
- XL600 Multi-line with 2.3" digits (starts at \$2,490)
- XL800 Alphanumeric with graphics (starts at \$3,790)

FREE 90-DAY TRIAL

XL is an easy and complete solution that will save you significant time and money. We'll prove it! Try an XL unit in your plant for 90 days. After 90 days, simply return it or pay for it.

CALL NOW! 1-877-767-LEAN

